

Beltane

2690A2MPC

OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100
1112054 Centexbel
Tested for harmful substances.
www.oeko-tex.com/standard100



VILOFT®

Protex.


Quick
Dry

Quick
Absorption

Anti-
Microbial

Flame retardant, anti-static T-shirt with long sleeves

Protect yourself from heat and flames down to your skin with this flame retardant and anti-static long sleeve T-shirt. Thanks to its great fit and moisture permeability, this is the ideal bodywear when working in potentially hazardous environments. The Beltane T-shirt has a round neck and elastic wristbands.



Flame retardant, anti-static T-shirt with long sleeves

Beltane - 2690A2MPC

European Standards:

- » EN ISO 11612 : 2015 / A1 B1 C1 F1
- » EN ISO 14116 : 2015 / IND.3
- » EN 1149-5 : 2018
- » EN ISO 13688 : 2013

Exterior:

- » Round neck
- » Long sleeves
- » Elasticated wristband
- » Back length 66 cm (L)

Fabric:

Jersey: 60% Protex® + 39% Viloft® + 1% AST; ± 180 g/m²

Sizes:

XS - 5XL

Colour:

- » B90 Navy Blue

Combining products:

2689

Packaging:

10 pieces per box

Wash and care instructions:



SIOEN head office

Fabriekstraat 23

B-8850 Ardooie

Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

www.sioen-ppc.com



**Discover
our products**

© 2020 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.