



## TEGERA® 8805 INFINITY

Cut resistant glove, nitrile foam, waterbased PU, palm-dipped, foam grip pattern, cut resistance level B, 18 gg, carbon, CRF® Technology, nylon, stainless steel fibre yarn, Cat. II, grey, yellow, withstands contact heat up to 100°C, DMF (DMFa) free, anatomically designed, for assembly work

### PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip in oily environments, extra comfortable

### SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 9

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11

COLLECTION Infinity

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile foam, waterbased PU

LINING MATERIAL 18 gg, Carbon, CRF® Technology, Nylon, Stainless steel fibre yarn

DEXTERITY 5

GRIP PATTERN Foam grip pattern

CUFF STYLE Knitwrist cuff

COLOR Grey, Yellow

PAIRS PER PACKAGE/CARTON 6/120

PIECES PER BOX 0

DISPLAY Hook OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION HPPE, stainless steel fibre yarn, carbon thread, nylon

1(3)

INFINITY™



CRF®



EAN NO.

5	8805-5	7340118328089
6	8805-6	7340118319322
7	8805-7	7340118319339
8	8805-8	7340118319346
9	8805-9	7340118319353
10	8805-10	7340118319308
11	8805-11	7340118319315

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
4X41B



EN 407:2004  
X1XXXX



## TEGERA® 8805 INFINITY

### FEATURES

Cut resistant according to 388:2016 level B, withstands contact heat up to 100°C, approved for handling foodstuffs, for touchscreen, anatomically designed

### PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

### PRIMARY ENVIRONMENTS OF USE

Dry environments, moist environments, dirty environments

### PRIMARY AREAS OF USE

Airport work, assembly, building and construction, carpentry, engineering, fine assembly, glass industry work, HVAC installation, installation work, machine driving, machine operating, metalwork, painting, paper industry work, repair work, service work, sheet-metal work, shop work, transport work, warehouse work

### PRIMARY INDUSTRIES OF USE

Pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

### TYPE OF WORK

Medium weight

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

#### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

**TEGERA® 8805 INFINITY**

**EU-TYPE EXAMINATION**

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07  
France

**COMPLIANCE DESCRIPTION**

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

**EN 388 – Testing**

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

CONFIDENCE IN TEXTILES Tested for harmful substances according to Oeko-Tex® Standard 100



**CE** Cat. II

EN 420:2003 + A1:2009



EN 388:2016 4X41B



EN 407:2004 X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com