

## TEGERA® 850

Synthetic glove, PU, palm-dipped, 13 gg, nylon, Cat. II, white, breathable back, water and oil repellent palm, for precision work

### PROPERTIES

Good fingertip sensitivity, good grip, good fit, breathable, light

### SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10

DIPPING Palm-dipped

DIPPING MATERIAL PU

LINING MATERIAL 13 gg, Nylon

DEXTERITY 5

CUFF STYLE Knitwrist cuff

LENGTH RANGE 220 - 270 mm

COLOUR White

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bulk pack OUTER MATERIAL SPECIFICATION Polyurethane

INNER MATERIAL SPECIFICATION Nylon



SIZE	ART. NO.	EAN NO.
5	850-5	7340118340791
6	850-6	7392626027237
7	850-7	7392626027244
8	850-8	7392626027251
9	850-9	7392626027268
10	850-10	7392626027275

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## TEGERA® 850

### FEATURES

Breathable back, water and oil repellent palm

### PREVENTS RISK OF

Abrasion injuries

### PRIMARY ENVIRONMENTS OF USE

Dry environments, clean environments, moist environments

### PRIMARY AREAS OF USE

Assembly, building and construction, carpentry, construction, inspection work, installation work, machine driving, machine operating, painting, repair work, shop work, warehouse work

### PRIMARY INDUSTRIES OF USE

Automotive, building and construction

### TYPE OF WORK

Light weight



**CE** Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
4121X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

**ejendals**  
PROTECTING HANDS AND FEET

### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

# TEGERA® 850

## EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07  
France

## COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

## EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
4121X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com