

## TECHNICAL DATASHEET

### 6230

|                |                           |
|----------------|---------------------------|
| MATERIAL       | Nylon carbon fabric, grey |
| COATING        | PU, white                 |
| SIZE(S)        | 5-11                      |
| PACKAGING UNIT | 240 pairs                 |
| CERTIFICATION  | EN 388, EN 16350          |




### DESCRIPTION

NITRAS antistatic gloves, grey, PU coating, partly coated on palm and fingertips, white, knitted wrist, integrated carbon fibre, antistatic (dissipative), touchscreen capable

|                        | Material                  | Colour |
|------------------------|---------------------------|--------|
| Palm                   | PU on nylon carbon fabric | White  |
| Index finger and thumb | PU on nylon carbon fabric | White  |
| Back of the hand       | Nylon carbon fabric       | Grey   |
| Fingertips             | PU on nylon carbon fabric | White  |
| Cuff / knitted wrist   | Nylon carbon fabric       | Grey   |

|             |        |     |        |       |       |            |       |
|-------------|--------|-----|--------|-------|-------|------------|-------|
| Size:       | 5      | 6   | 7      | 8     | 9     | 10         | 11    |
| Hem colour: | purple | red | yellow | brown | black | light blue | white |

| EN 420:2003 + A1:2009   |                                   | Test parameter                    | Performance level | Test result                          |
|---|-----------------------------------|-----------------------------------|-------------------|--------------------------------------|
|   |                                   | Dexterity                         | 1-5               | 5                                    |
| EN 388:2016   |                                   | Test parameter                    | Performance level | Test result                          |
| <br><b>3141X</b> | Abrasion resistance               |                                   | 1-4               | 3                                    |
|   | Blade cut resistance (Coupe-Test) |                                   | 1-5               | 1                                    |
|   | Tear resistance                   |                                   | 1-4               | 4                                    |
|   | Puncture resistance               |                                   | 1-4               | 1                                    |
|   | Blade cut resistance (TDM)        |                                   | A-F               | X                                    |
| EN 16350:2014   |                                   | Test parameter                    | Performance level | Test result                          |
|   |                                   | Palm (resistance [Q])             | -                 | 2,46 x 10 <sup>5</sup> (dissipative) |
|   |                                   | Back of the hand (resistance [Q]) | -                 | 4,84 x 10 <sup>4</sup> (dissipative) |