



SIZE	ART. NO.	EAN NO.
7	683A-7	7340118316628
8	683A-8	7340118316642
9	683A-9	7340118316666
10	683A-10	7340118316581
11	683A-11	7340118316604

TEGERA® 683A

Synthetic glove, nitrile, 3/4 dipped, sandy finish, 10 gg, 13 gg, acrylic, polyester, Cat. II, black, yellow, high visibility colour, water and oil repellent palm and knuckle, for allround work

PROPERTIES

Good grip in oily environments, warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 7, 8, 9, 10, 11

DIPPING 3/4 dipped

DIPPING MATERIAL Nitrile

LINING MATERIAL 10 gg, 13 gg, Acrylic, Polyester

DEXTERITY 5

GRIP PATTERN Sandy finish

CUFF STYLE Knitwrist cuff

LENGTH RANGE 240-280 mm

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL

SPECIFICATION Nitrile, polyester

INNER MATERIAL SPECIFICATION Acrylic

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 683A

FEATURES

High visibility colour, water and oil repellent palm and knuckle

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with moisture, contact with oil, contact with cold

PRIMARY ENVIRONMENTS OF USE

Outdoors, dry environments, cold environments, wet environments, moist environments, oily and greasy environments

PRIMARY AREAS OF USE

Assembly, building and construction, fishing industry work, foodstuff handling, gardening, warehouse work

PRIMARY INDUSTRIES OF USE



Agriculture, oil, gas, petrochemical, machinery and equipment, MRO, building and construction

TYPE OF WORK

Heavy weight



CE Cat. II

EN 420:2003 + A1:2009  EN 388:2016 3231X  EN 407:2004 X2XXXX

 EN 511:2006 02X  

Contact heat valid for coated area only

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-25

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 683A

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)


EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 511:2006 Protective gloves against cold

Suitable for contact with foodstuffs, except for fatty foods



CE Cat. II

EN 420:2003 + A1:2009  EN 388:2016 3231X  EN 407:2004 X2XXXX

 EN 511:2006 02X  

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.