

## TEGERA® 9295

Synthetic leather glove, unlined, 0,8 mm Macrothan®, polyester, Cat. II, black, grey, yellow, wrist support, chrome free, hook-and-loop, for allround work

### PROPERTIES

Durable, perfect fit, extra comfortable

### SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

COLLECTION PRO

PALM MATERIAL Macrothan®

PALM THICKNESS 0,8 mm

BACK MATERIAL Polyester

LINING Unlined

DEXTERITY 5

CUFF STYLE Wrist-supporting cuff

FASTENING Hook-and-loop

LENGTH RANGE 236-277 mm

COLOUR Black, Grey, Yellow

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL SPECIFICATION Polyurethane, polyester



MacroThan®

reddot design award  
winner 2007

SIZE	ART. NO.	EAN NO.
8	9295-8	7392626023581
9	9295-9	7392626023598
10	9295-10	7392626023604
11	9295-11	7392626027305

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
3141X



## TEGERA® 9295

### FEATURES

Wrist-supporting, extra long, chrome free, reinforced index finger, reinforced palm, reinforced seams, reinforced fingertips, reinforced fingers and thumb, padded palm, pre-curved fingers, specially designed thumb, knuckle protection, ergonomically shaped, reflector, soft, specially designed details

### PREVENTS RISK OF

Chrome allergy, wrist injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping

### PRIMARY ENVIRONMENTS OF USE

Dry environments, dirty environments

### PRIMARY AREAS OF USE

Airport work, building and construction, construction, engineering, inspection work, machine driving, machine operating, soil preparation, transport work, warehouse work

### PRIMARY INDUSTRIES OF USE

Machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

### TYPE OF WORK

Medium weight

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

#### EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

## TEGERA® 9295

### EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

### COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

### EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
3141X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-21

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com