



TEGERA® 777

Synthetic glove, PU, palm-dipped, smooth finish, 18 gg, nylon, Cat. II, black, blue, ultra thin, breathable back, water and oil repellent palm

PROPERTIES

Extremely good fingertip sensitivity, extra flexible, durable, good grip, perfect fit, extra comfortable, very breathable, extremely light

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11

DIPPING Palm-dipped

DIPPING MATERIAL PU

LINING MATERIAL 18 gg, Nylon

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Rolled edges

LENGTH RANGE 220-270mm

COLOUR Black, Blue

PAIRS PER PACKAGE/CARTON 6/120

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL SPECIFICATION Polyurethane

INNER MATERIAL SPECIFICATION Nylon

SIZE	ART. NO.	EAN NO.
6	777-6	7340118320786
7	777-7	7340118320809
8	777-8	7340118320823
9	777-9	7340118320847
10	777-10	7340118320748
11	777-11	7340118320762
5	777-5	7340118325392

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 777

FEATURES

Breathable back, water and oil repellent palm, ultra thin

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, contact with dirt, drying out

PRIMARY ENVIRONMENTS OF USE

Dry environments, oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

Fine assembly

PRIMARY INDUSTRIES OF USE

Machinery and equipment, MRO, automotive, utilities, facilities

TYPE OF WORK

Light weight

2(3)

CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3111X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 777

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3111X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

3(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com