

## TEGERA® 8803 INFINITY

Synthetic glove, nitrile, nitrile foam, waterbased PU, 3/4 dipped, double-dipped, foam grip pattern, 18 gg, nylon, spandex, Cat. II, black, yellow, withstands contact heat up to 100°C, DMF (DMFa) free, oil and grease resistant, waterproof palm, for assembly work

### PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip in oily environments, extra comfortable

### SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

COLLECTION Infinity

DIPPING 3/4 dipped, double-dipped

DIPPING MATERIAL Nitrile, nitrile foam, waterbased PU

LINING MATERIAL 18 gg, Nylon, Spandex

DEXTERITY 5

GRIP PATTERN Foam grip pattern

CUFF STYLE Knitwrist cuff

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/120

PIECES PER BOX 0

DISPLAY Hook OUTER MATERIAL SPECIFICATION Nitrile

INNER MATERIAL SPECIFICATION Nylon, elastane



I N F I N I T Y™



SIZE	ART. NO.	EAN NO.
7	8803-7	7340118319025
8	8803-8	7340118319032
9	8803-9	7340118319049
10	8803-10	7340118319001
11	8803-11	7340118319018
6	8803-6	7340118383989

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE Cat. II

EN 420:2003  
+ A1:2009



EN 388:2016  
4121X



EN 407:2004  
X1XXXX



## TEGERA® 8803 INFINITY

### FEATURES

Withstands contact heat up to 100°C, approved for handling foodstuffs, oil and grease resistant, waterproof palm, anatomically designed

### PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with moisture, contact with oil and fat

### PRIMARY ENVIRONMENTS OF USE

Dry environments, wet environments, moist environments, oily and greasy environments, dirty environments

### PRIMARY AREAS OF USE

Airport work, assembly, building and construction, carpentry, engineering, fine assembly, HVAC installation, installation work, machine driving, machine operating, repair work, service work, shop work, transport work, warehouse work

### PRIMARY INDUSTRIES OF USE

Machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

### TYPE OF WORK

Medium weight

2(3)

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

**TEGERA® 8803 INFINITY**

**EU-TYPE EXAMINATION**

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07  
France

**COMPLIANCE DESCRIPTION**

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

**EN 388 – Testing**

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

CONFIDENCE IN TEXTILES Tested for harmful substances according to Oeko-Tex® Standard 100



**CE** Cat. II

EN 420:2003 + A1:2009



EN 388:2016 4121X



EN 407:2004 X1XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-22

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com